## MATERIAL SAFETY DATA SHEET (MSDS)

## Cal-CM Plus Mini Prilled Calcium Sulfate

SECTION I IDENTITY (As used on label and list)

Manufacturing Facility:

ART WILSON CO. CAL-CM PLUS

PO BOX 20160 MINI PRILLED CALCIUM SULFATE

CARSON CITY, NV 89721-0160

SECTION II HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

Hazardous components (specific chemical identity, common names OSHA PEL / ACGIH TLV / other limits recommended % optional)

NONE

SECTION III	PH	PHYSICAL / CHEMICAL CHARACTERISTICS				
Boiling Point Vapor Pressure (mm Hg) Vapor Density Air =1) Solubility in Water Appearance and Odor	NONE NONE NONE 0.2%	Specific Gravity (H <sub>2</sub> O = 1)  Melting Point  Evaporation Rate (Butyl Acetate = 1)	2.5% 1,450° C NONE			

SECTION IV FIRE AND EXPLOSION HAZARD DATA

Flash Point (method used) NON-FLAMMABLE

SECTION V		REACTIVITY DATA			
Stability	STABLE	Conditions to Avoid	NONE		
	Incompatibility (materials to avoid)	ACIDS	Hazardous Decomposition or By-Products	NONE	
	Hazardous Polymerization	WILL NOT OCCUR	Conditions to Avoid	NONE	

SECTION VI HEALTH HAZARD DATA

NON-HAZARDOUS

SECTION VII PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be taken in case material is released or spilled

Waste Disposal Method

Precautions to be taken in handling and storing

SWEEP UP AND REMOVE

TRANSPORT TO LAND FILL OR SPREAD ON AGRICULTURAL ACREAGE

WEAR DUST MASK IN DUSTING CONDITION

SECTION VIII CONTROL MEASURES

Respiratory Protections (specify)

**NOT REQUIRED**